


JC

Femelle tournant ORFS

ISO 12151-1 – SWSA
SAE J516 – ORFS




XXXXX-XX-XX Référence 73	D. Int. du tuyau				Filetage UNF	A	B	H	W
	DN	pouce	module	mm		mm	mm	mm	mm
1JC73-12-12-SM	20	3/4	-12	19,1	1-3/16x12	81	33	30	36
1JC73-16-16-SM	25	1	-16	25,4	1-7/16x12	97	38	36	41
1JC73-20-20-SM	32	1-1/4	-20	31,8	1-11/16x12	106	42	46	50
1JC73-24-24-SM	40	1-1/2	-24	38,1	2x12	117	44	50	60

JS

Femelle tournant ORFS

ISO 12151-1-SWSB
SAE J516 – ORFS



XXXXX-XX-XX Référence 73	D. Int. du tuyau				Filetage UNF	A	B	H	W
	DN	pouce	module	mm		mm	mm	mm pouce	mm pouce
1JS73-12-12-SM	20	3/4	-12	19,1	1-3/16x12	98	50	30	36
1JS73-16-12-SM	20	3/4	-12	19,1	1-7/16x12	103	58	1-3/8	1-5/8
1JS73-16-16-SM	25	1	-16	25,4	1-7/16x12	103	52	36	41
1JS73-20-16-SM	25	1	-16	25,4	1-11/16x12	114	64	41	50
1JS73-20-20-SM	32	1-1/4	-20	31,8	1-11/16x12	118	54	46	50
1JS73-24-24-SM	40	1-1/2	-24	38,1	2x12	120	57	50	60

Série d'embouts compatible avec les tuyaux:

SM: 6 pans métrique

73 731