

Safety Light Curtains

Point of Operation Control

Product Selection

3. Programmable Interface—Optional

	Input Voltage	Reset	Floating Blanking	Fixed Blanking	PSDI	Muting	Outputs	More Details	Catalogue Number
	24V DC	Manual/ Automatic	yes	yes	yes	yes	2 PNP OSSD 1 Aux. PNP	2-60	440L-M8100

4. Safety Relay Interfaces—Required

	Input Voltage	Reset	Floating Blanking	Fixed Blanking	PSDI	Muting	Outputs	More Details	Catalogue Number
	24V DC	Manual/ Automatic	no	no	no	no	4 amp 2 N.O. Safety 1 N.C. Aux.	2-58	440L-M8200

Note: For wiring refer to Safeguarding Applications section of this catalogue.

5. Safety Relay Interfaces—Optional

Relay	Input	Safety Outputs	Auxiliary Outputs	Terminals	Power Supply	Reset	Catalogue Number
 MSR127RP	1NC, 2NC, or Light Curtain	3 N.O.	1 N.C.	Removable	24V AC/DC	Automatic/Manual	440R-N23132
						Monitored Manual	440R-N23135
					115V AC	Automatic/Manual	440R-N23131
						Monitored Manual	440R-N23134
					230V AC	Automatic/Manual	440R-N23130
					Monitored Manual	440R-N23133	
 MSR126	Light Curtain or Single Channel (MSR126T)	2 N.O.	None	Fixed	24V AC/DC	Automatic/Manual	440R-N23117
					115V AC		440R-N23116
	230V AC				440R-N23115		
	24V AC/DC				440R-N23114		
	115V AC				440R-N23113		
	230V AC				440R-N23112		
	Light Curtain or Single Channel (MSR126R)				24V AC/DC	Monitored Manual	440R-N23123
					115V AC		440R-N23122
					230V AC		440R-N23121
					24V AC/DC		440R-N23120
					115V AC		440R-N23119
					230V AC		440R-N23118
 MSR131RTP	Light Curtain or Safety Mat	3 N.O.	2 N.C. 2 PNP Solid State	Removable	24V AC/DC	Automatic/Manual or Monitored Manual	440R-C23139
					115V AC		440R-C23137
					230V AC		440R-C23136