



FG Mâle fixe cône 24° – série gaz



XXXXX-XX-XX		D. Int. du tuyau				Filetage métrique	D. Ext. du tube mm	A mm	B mm	H mm
Référence		DN	pouce	module	mm					
 46										
1FG46-13-5	1FG48-13-5	8	5/16	-5	7,9	M20x1,5	13	53	29	22
1FG46-13-6	1FG48-13-6	10	3/8	-6	9,5	M20x1,5	13	52	30	22
1FG46-17-8	1FG48-17-8	12	1/2	-8	12,7	M24x1,5	17	51	27	24
1FG46-21-10	1FG48-21-10	16	5/8	-10	15,9	M30x1,5	21	58	32	30
1FG46-27-12	1FG48-27-12	20	3/4	-12	19,1	M36x1,5	27	60	34	36
1FG46-33-16	1FG48-33-16	25	1	-16	25,4	M45x1,5	33	69	40	46

F2 Femelle tournant gaz coude 90°



XXXXX-XX-XX		D. Int. du tuyau				Filetage métrique	D. Ext. du tube mm	A mm	B mm	E mm	W mm
Référence		DN	pouce	module	mm						
 46											
1F246-13-5	1F248-13-5	8	5/16	-5	7,9	M20x1,5	13	59	35	30	24
1F246-13-6	1F248-13-6	10	3/8	-6	9,5	M20x1,5	13	60	38	33	24
1F246-17-8	1F248-17-8	12	1/2	-8	12,7	M24x1,5	17	61	37	43	30
1F246-21-10	1F248-21-10	16	5/8	-10	15,9	M30x1,5	21	71	46	45	36

Série d'embouts compatible avec les tuyaux:

Aussi disponible en acier inoxydable. Voir catalogue 4400.1

 46	ou		441	441RH	461LT	462	462ST													
 46	463	492	492ST	692	692TWIN															
 48	301SN	301TC	302	304	351TC	421RH	421SN	421WC	422	426	436	451	451TC	471TC	472TC	477	477ST	493	811	881