


For hose types: 781 / 78C / 782


C9 - DIN 20 078 P Heavy Series Metric Swivel Female



XXXX-XX-XX Part Number	Hose-I.D.				Thread metric	Tube O.D. mm	A mm	B mm	W mm
	DN	Inch	Size	mm					
1C978-20-12	20	3/4	-12	19,1	M30x2	20	81	33	36
1C978-25-12	20	3/4	-12	19,0	M36x2	25	80	32	46
1C978-20-16	25	1	-16	25,4	M30x2	20	86	36	36
1C978-30-16	25	1	-16	25,4	M42x2	30	87	36	50
1C978-30-20	32	1-1/4	-20	31,8	M42x2	30	106	42	50
1C978-38-20	32	1-1/4	-20	31,8	M52x2	38	102	35	60
1C978-38-24	40	1-1/2	-24	38,1	M52x2	38	105	40	60

Fittings with standard O-Ring seals can be used for temperatures from -30 °C up to +105 °C.
Find O-Rings in section I. Special O-Rings are available on request.

0C - DIN 20 078 P Heavy Series Metric Swivel Female 45° Elbow



XXXX-XX-XX Part Number	Hose-I.D.				Thread metric	Tube O.D. mm	A mm	B mm	E mm	W mm
	DN	Inch	Size	mm						
10C78-20-12	20	3/4	-12	19,1	M30x2	20	112	64	28	36
10C78-25-12	20	3/4	-12	19,0	M36x2	25	113	65	29	46
10C78-30-16	25	1	-16	25,4	M42x2	30	126	73	34	50
10C78-38-20	32	1-1/4	-20	31,8	M52x2	38	161	97	37	60
10C78-38-24	40	1.1/2	-24	38,1	M52x2	38	175	113	42	60

Fittings with standard O-Ring seals can be used for temperatures from -30 °C up to +105 °C.
Find O-Rings in section I. Special O-Rings are available on request.

Material: zinc plated - yellow chromated mild steel

Only items priced in current price list are carried in stock.
Dimensions shown may be changed at any time without prior notice.